

Material Declaration for G125-FWXXXXXF94

Product Information	
Part Number:	G125-FW1XXXXF94
Part Description:	2 x Female Crimped Wire 26AWG
Part Weight (g):	(0.00198 * XXXX) + 0.0284

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0268	1%	Copper	7440-50-8
	0.00052	0.5%	Beryllium	7440-41-7
	0.00011	0.5%	Lead	7439-92-1
	0	0.000082g max	Nickel (impurity only)	7440-02-0
	0	0.000082g max	Cobalt (impurity only)	7440-48-4
	0	0.000054g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	0.000054g max	Aluminium (impurity only)	7429-90-5
	0	0.000054g max	Silicon (impurity only)	7440-21-3
	0	0.000136g max	Other Impurities	
	0.000204	5%	Gold	7440-57-5
	0.00075	10%	Nickel	7440-02-0
Wire	0.000706 * XXXX	10%	Copper	7440-50-8
Wire - Plating	0.000083 * XXXX	10%	Silver	7440-22-4
Wire - Insulation	0.00119 * XXXX	10%	PTFE	9002-84-0

Product Information	
Part Number:	G125-FW2XXXXF94
Part Description:	2 x Female Crimped Wire 28AWG
Part Weight (g):	(0.00157 * XXXX) + 0.0284

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0268	1%	Copper	7440-50-8
	0.00052	0.5%	Beryllium	7440-41-7
	0.00011	0.5%	Lead	7439-92-1
	0	0.000082g max	Nickel (impurity only)	7440-02-0
	0	0.000082g max	Cobalt (impurity only)	7440-48-4
	0	0.000054g max	Iron (impurity only)	7439-89-6
Contacts - Plating	0	0.000054g max	Aluminium (impurity only)	7429-90-5
	0	0.000054g max	Silicon (impurity only)	7440-21-3
	0	0.000136g max	Other Impurities	
	0.000204	5%	Gold	7440-57-5
	0.00075	10%	Nickel	7440-02-0
Wire	0.0005 * XXXX	10%	Copper	7440-50-8
Wire - Plating	0.000059 * XXXX	10%	Silver	7440-22-4
Wire - Insulation	0.00101 * XXXX	10%	PTFE	9002-84-0

Material Declaration for G125-FWXXXXXF94

Product Information	
Part Number:	G125-FW3XXXXF94
Part Description:	2 x Female Crimped Wire 30AWG
Part Weight (g):	(0.00123 * XXXX) + 0.0284


Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0268	1%	Copper	7440-50-8
	0.00052	0.5%	Beryllium	7440-41-7
	0.00011	0.5%	Lead	7439-92-1
	0	0.000082g max	Nickel (impurity only)	7440-02-0
	0	0.000082g max	Cobalt (impurity only)	7440-48-4
	0	0.000054g max	Iron (impurity only)	7439-89-6
	0	0.000054g max	Aluminium (impurity only)	7429-90-5
Contacts - Plating	0	0.000054g max	Silicon (impurity only)	7440-21-3
	0	0.000136g max	Other Impurities	
	0.000204	5%	Gold	7440-57-5
	0.00075	10%	Nickel	7440-02-0
Wire	0.000312 * XXXX	10%	Copper	7440-50-8
Wire - Plating	0.000037 * XXXX	10%	Silver	7440-22-4
Wire - Insulation	0.00088 * XXXX	10%	PTFE	9002-84-0

Product Information	
Part Number:	G125-FW4XXXXF94
Part Description:	2 x Female Crimped Wire 32AWG
Part Weight (g):	(0.00103 * XXXX) + 0.0284

Process Data	
Peak Reflow (Deg. C)	n/a
Termination Finish	n/a
RoHS Compliant? (Y/N)	Yes

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Beryllium Copper	0.0268	1%	Copper	7440-50-8
	0.00052	0.5%	Beryllium	7440-41-7
	0.00011	0.5%	Lead	7439-92-1
	0	0.000082g max	Nickel (impurity only)	7440-02-0
	0	0.000082g max	Cobalt (impurity only)	7440-48-4
	0	0.000054g max	Iron (impurity only)	7439-89-6
	0	0.000054g max	Aluminium (impurity only)	7429-90-5
Contacts - Plating	0	0.000054g max	Silicon (impurity only)	7440-21-3
	0	0.000136g max	Other Impurities	
	0.000204	5%	Gold	7440-57-5
	0.00075	10%	Nickel	7440-02-0
Wire	0.00025 * XXXX	10%	Copper	7440-50-8
Wire - Plating	0.000029 * XXXX	10%	Silver	7440-22-4
Wire - Insulation	0.000748 * XXXX	10%	PTFE	9002-84-0

Prepared by: 

Martin J Perry, BSc(Eng) MSc CEng MIET
Compliance Consultant
ComplianceTeam@harwin.co.uk

On behalf of:

