




HARWIN

 **Datamate®**

Datamate PIHR - Pin in Hole Reflow


INDUSTRY RECOGNISED, PROVEN PERFORMANCE



[Datamate](#) is the field-proven high-reliability range of choice for many industries.

- Complies with British Standard 9525-F0033 (1 & 2-row) and CECC 75101-008 (1, 2 & 3-row);
- Designed with aerospace, military and other "high-end" applications in mind;
- Proven in many years of successful service;
- Successfully and internationally utilized in COTS programs.

DATAMATE PIHR - DESIGNED FOR AUTOMATED ASSEMBLY



Datamate connectors typically have 3mm terminations, to give robust throughboard connection with wave soldered or hand soldered joints on the underside of the PCB.

Datamate PIHR has been designed for throughboard reflow, known also as Pin-In-Hole Reflow (PIHR) or Pin-In-Paste (PIP). This enables throughboard connections to work better with automated assembly processes, while maintaining robust connection to the PCB.


DATAMATE PIHR - DESIGNED FOR AUTOMATED ASSEMBLY



All Datamate PIHR connectors are supplied on Tape and Reel, and are fitted with Pick and Place caps.

This makes them suitable for volume manufacturing and automated placement with vacuum nozzles. Product placement on the PCB is carried out at the same time as all the SMT or other reflow components on the board. No secondary operation required to accommodate the throughboard connector.


FEATURES – SECURE MATING CONNECTIONS



The Datamate L-Tek connectors use simple locking latches made from high strength Beryllium Copper. Mating is fast and simple – just push the two connectors together, and the latches snap into place. The connectors are then locked together and require manual deflection of the latches to separate.

These latches assure that the connection performs to the maximum vibration, shock, bump and acceleration, and provide cable strain relief.


FEATURES – SHROUDING AND POLARISATION



Latches removed for visibility

Connectors are shrouded, to prevent accidental damage to the miniature contacts. They also incorporate polarization, which prevents connectors being mated the wrong way round.

FULL COMPATIBILITY WITH DATAMATE L-TEK



Datamate PIHR is compatible with all female Datamate L-Tek connectors with the same contact arrangement. The 4-fingered Beryllium Copper female contact gives superb performance, for both electrical and mechanical specifications. This inner "contact clip" is stamped and plated with a durable gold finish at our UK headquarters. The spring performance of the contact gives the environmental resistance to shock and vibration, with a temperature range up to 125°C.

TOOLING



The [Z80-299](#) tool is available to help deflect the latches when separating the mated connectors.

Datamate®

CURRENT RANGE - DATAMATE L-TEK



Currently 2 sizes of PIHR are available from Harwin:

- [M80-7720242R](#) – 2 contacts
- [M80-7720342R](#) – 3 contacts

[Contact us](#) if you have other product requirements.

ELECTRICAL SPECIFICATIONS

Current Rating	3.3A max (single contact) 3.0A max (all contact)
Working Voltage	800V DC or AC _{peak}
Voltage Proof (Maximum Voltage)	1,200V DC or AC _{peak}

The Datamate range is a professional connector system aimed at Commercial or COTS prices. It is field-proven in tough terrains and environments, from underground to outer space. The current rating exceeds the levels normally expected from a 2mm pitch connector system.

The full [Datamate Component Specification](#) is available to download from the Harwin website.

MECHANICAL & ENVIRONMENTAL SPECIFICATIONS

Vibration	10g for 6 hours
Shock	100g
Durability	500 mating cycles
Temperature Range	-55°C to +125°C

The above specifications secure the reputation of the Datamate range as a High-Reliability connector. Multiple Test Reports for Datamate are available from individual product pages at Harwin.com.

MARKETS



Rugged, high-reliability connectors continue to be in strong demand in many varied environments. Small enough to be used in handheld and portable applications, yet high-powered enough to meet the demands of large-scale equipment, Datamate continues to find new applications and new product uses in existing and new customers.

- Aerospace
- Autosport
- Military
- Robotics
- Oil & Gas

Learn more about our other ranges



HIGH RELIABILITY
WITH SUPREME
PERFORMANCE



INNOVATIVE
DESIGNS FOR
EASY ASSEMBLY



DEPENDABLE
CONNECTIVITY
ACROSS THE BOARD

Find out more about our full range
of inter-connection solutions at

www.harwin.com

HRI
RANGE

EZI
RANGE

BBi
RANGE

Get Help from a Harwin Expert

Our experts are specialists in their field with many years of experience in their respective roles and industries.

Find an expert that can help you with your enquiry.

[Click Here >>](#)

CAD Models and Evaluation Samples also available at www.harwin.com



Contact Us

Europe, Middle East & Africa

T: +44 (0)23 9231 4545

E: technical@harwin.com

Americas

T: +1 603 893 5376

E: technical-us@harwin.com

Asia Pacific

T: +65 6 779 4909

E: technical-asia@harwin.com

WWW.HARWIN.COM